



TITANIUM DIOXIDE RC 82

Type

RC 82 is a micronized rutile pigment produced by the sulphate process by CINKARNA CELJE - SLOVENIA. The pigment is lattice-stabilized with alumina and surface-treated with aluminium and silicon compounds.

Applications

- dispersion paints,
- industrial and decorative coatings,
- primers,
- wallpaper coatings
- plaster paints based on synthetic resins,
- road marking paints,
- powder coatings,
- coloured decorative papers,
- carton-paper coatings,
- electrodes,
- tiles.

Technical data parameter

TiO₂ content	min 94.0 %	ISO 591-1
Classification	R2	ISO 591
Oil absorption	18 – 21 g/100 g	ISO 787-5
Humidity (by packing)	max 0.5 %	ISO 787-2
pH	7.0 – 8.0	ISO 787-9
Sieve residue (µm40)	max 0.01 %	ISO 787-7
CIE Lab (powder)		
L*	min 97.5	Internal Method
b*	max 2.5	Internal Method

Packaging

- 25 kg multiply paper sacks, packed 40 sacks per pallet, ordinary or water-soluble, wrapped with stretch-hood foil, suitable for recycling.
- Big bags up to 1000 kg
- Bulk road tankers containing up to 23 t by request.