



## Technical Data Sheet

# CC MASTER PE 90250 P LL

### Type

CC Master PE 90250 P LL is concentrate of titanium dioxide, on the basic of linear low density polyethylene.

### Applications

The product is used for the mass colouration of polyolefin polymers.

### Technical data parameter

<b>Colour shade</b>	White 902	
<b>Appearance</b>	Underwater cutting granules	
<b>Density</b>	1,60 – 1,75 g/cm <sup>3</sup>	ISO 1183
<b>Bulk density</b>	0,95 – 1,05 g/cm <sup>3</sup>	ISO 3953
<b>MFI ( 190 °C, 2.16 kg )</b>	4 – 8 g/10 min	ISO 1133
<b>Pigment content</b>	50 ±1 %	
<b>Filler content</b>	YES	
<b>MFI of carrier</b>	15– 30 g/10 min	ISO 1133
<b>Density of carrier</b>	0,91 – 0,94 g/cm <sup>3</sup>	ISO 1183
<b>Masterbatch is in compliance with</b>	Commission Regulation (EU) No. 10/2011 of 14 th January 2011 on plastic materials and articles intended to come into contact with food	
<b>Storing</b>	24 months in a dry place at room temperature	

*Those parameter values are universal and are not necessarily the same parameter in the specification for each product.*

### Packaging

- 25 kg PE valve bags, packed 40 or 50 bags per pallet covered with foil and wrapped with shrinkable foil.
- Big-bags up to 1000 or 1250 kg.
- Octabin with inner polyethylene bag, up to 1000 or 1250 kg.
- Bulk road tankers containing up to 26 t by request.

<p><i>Technical information are the result of knowledge based on laboratory work and practical experience. In the case of use of the product outside of our control we can't assume any responsibility and guarantee only the quality of the product as such. We reserve the right to make changes without prior notice.</i></p>
--